

/DIAG/G

SYSTEM CONFIGURATION GENERATE

CONFIGURATION OF TEST HEAD

PIN CONFIGURATION 1. 480DR+320I/O(HALF)
 2. 768DR+512I/O(FULL)
 3. 960DR+640I/O(FULL)
 4. 240DR+160I/O(QUARTER) [1-4] ...> 3

NUMBER OF TEST HEAD [1,2]> 2

CONFIGURATION OF TEST HEAD 1

PE BOARD TYPE 0.NO BOARD
 1.BGM-023206X04 (DR+IO PE,x2 AMP)
 2.BGM-023206X05 (DR PE,x2 AMP)

	PIN	1	13	25
CHILD A1	>	1	1	1
CHILD A3	>	1	1	1
CHILD B1	>	1	1	1
CHILD B3	>	1	1	1
CHILD C1	>	1	1	1
CHILD C3	>	1	1	1
CHILD D1	>	1	1	1
CHILD D3	>	1	1	1
CHILD E1	>	1	1	1
CHILD E3	>	1	1	1
CHILD F1	>	1	1	1
CHILD F3	>	1	1	1
CHILD G1	>	1	1	1
CHILD G3	>	1	1	1
CHILD H1	>	1	1	1
CHILD H3	>	1	1	1

CONFIGURATION OF TEST HEAD 2

PE BOARD TYPE 0.NO BOARD
 1.BGM-023206X04 (DR+IO PE,x2 AMP)
 2.BGM-023206X05 (DR PE,x2 AMP)

	PIN	1	13	25
CHILD A1	>	1	1	1
CHILD A3	>	1	1	1
CHILD B1	>	1	1	1
CHILD B3	>	1	1	1
CHILD C1	>	1	1	1
CHILD C3	>	1	1	1
CHILD D1	>	1	1	1
CHILD D3	>	1	1	1
CHILD E1	>	1	1	1
CHILD E3	>	1	1	1

CHILD F1	>	1	1	1
CHILD F3	>	1	1	1
CHILD G1	>	1	1	1
CHILD G3	>	1	1	1
CHILD H1	>	1	1	1
CHILD H3	>	1	1	1

CONFIGURATION OF DPU

1'ST DPU	:	STN 1,2	[Y,N]	>	YES
TEST HEAD 1		DC	CONFIGURATION	[1-32]	> 1-32
		PPS	CONFIGURATION	[1-128]	> 1-64
TEST HEAD 2		DC	CONFIGURATION	[1-32]	> 1-32
		PPS	CONFIGURATION	[1-128]	> 1-64
AC FREQUENCY (Hz)		[50,60]		>	50

CONFIGURATION OF FTU

FLASH OPTION	[Y,N]	>	YES
--------------	-------	--------	-----

CONFIGURATION OF FM

TYPE OF FM	[1:NORMAL(AFM), 2:MRA4(FMRA)]	>	1
NUMBER OF AFM BOARD	[0-8]	>	8
SIZE OF AFM BOARD	[1:1G, 2:4G]	>	1
PM(PATTERN MEMORY) BOARD EXIST	[Y,N]	>	YES
SIZE OF PM BOARD	[1:576M]	>	1

END SAVE

/LOG OFF